

Applicants: Goldberg et al.
Application No.: 10/730,671

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently amended): A method for coordinating the use of beam forming between two communicating entities wherein control information regarding the use of beam forming is not communicated between the two entities, the method comprising the steps of:

selecting one of the two communicating entities for reduction of its beam adjustment;

measuring an error in the alignment of beams emanating from the two communicating entities;

determining a correction factor that is a fraction of said measured error; and

adjusting the beam of the selected entity in an amount equal to the correction factor ~~a fraction of the error measured~~, whereby ~~the beams emanating from the two communicating entities are aligned with respect to each other~~ said adjusted beam is aligned with the beam transmitted by the unselected communicating entity.

2. (Original): The method of claim 1 wherein the two communicating entities are a base station and a WTRU.

Applicants: Goldberg et al.
Application No.: 10/730,671

3. (Original): The method of claim 1 wherein the two communicating entities are two WTRUs.
4. (Original): The method of claim 1 further comprising the step of:
repeating the measuring and adjusting steps until the error measured is below a predetermined value.
5. (Original): The method of claim 1 wherein the fraction is 0.5.
6. (Original): The method of claim 1 wherein the error measurement and beam adjustment is performed in the azimuth dimension.
7. (Original): The method of claim 1 wherein the error measurement and beam adjustment is performed in the elevation dimension.
8. (Original): The method of claim 1 wherein the error measurement and beam adjustment is performed in the azimuth and elevation dimensions.
9. (Currently amended): A method for coordinating the use of beam forming between two communicating entities wherein control information regarding the use of beam forming is communicated between the two entities, the method comprising the steps of:
measuring an error in the alignment of beams emanating from the two communicating entities;
determining a correction factor a fraction of said measured error for each of the entities wherein the sum of the two correction factors is equal to one;

Applicants: Goldberg et al.
Application No.: 10/730,671

~~measuring an error in the alignment of beams emanating from the two communicating entities;~~

communicating the correction measurement between the entities; and

adjusting the beam of both entities according to their respective correction factors, whereby ~~the beams emanating from the two communicating entities are aligned with respect to each other~~ the adjusted beam is aligned with the beam transmitted by the unselected communicating entity.

10. (Original): The method of claim 9 wherein the two communicating entities are a base station and a WTRU.

11. (Original): The method of claim 9 wherein the two communicating entities are two WTRUs.

12. (Original): The method of claim 9 wherein the error measurement and beam adjustment is performed in the azimuth dimension.

13. (Original): The method of claim 9 wherein the error measurement and beam adjustment is performed in the elevation dimension.

14. (Original): The method of claim 9 wherein the error measurement and beam adjustment is performed in the azimuth and elevation dimensions.

15. (Original): The method of claim 9 wherein the correction factor of one entity is zero thereby causing said entity to refrain from adjusting its beam.

Applicants: Goldberg et al.
Application No.: 10/730,671

16. (Currently amended): A method for coordinating the use of beam forming between two communicating entities wherein control information regarding the use of beam forming is not communicated between the two entities, the method comprising the steps of:

selecting one of the two communicating entities for reduction of its beam adjustment;

measuring an error in the alignment of beams emanating from the two communicating entities; ~~and~~

determining a correction factor that is a fraction of said measured error; and

the unselected communicating entity refraining from adjusting its beam and the ~~other~~ selected communicating entity adjusting its beam in accordance with said correction factor whereby the adjusted beam is aligned with the beam transmitted by the unselected communicating entity.

17. (Original): A method for coordinating the use of beam forming between two communicating entities wherein control information regarding the use of beam forming is communicated between the two entities, the method comprising the steps of:

measuring an error in the alignment of beams emanating from the two communicating entities in the azimuth dimension;

measuring an error in the alignment of beams emanating from the two communicating entities in the elevation dimension;

determining ~~selecting~~ a first correction factor based on said measured error in the azimuth dimension for each of the entities for use in the azimuth dimension wherein the sum of the two first correction factors is equal to one;

Applicants: Goldberg et al.
Application No.: 10/730,671

~~determining selecting~~ a second correction factor based on said measured error in the elevation dimension for each of the entities for use in the elevation dimension wherein the sum of the two second correction factors is equal to one;

~~measuring an error in the alignment of beams emanating from the two communicating entities in the azimuth dimension;~~

~~measuring an error in the alignment of beams emanating from the two communicating entities in the elevation dimension;~~

adjusting the beam of both entities according to their respective first correction factors wherein an error is detected in the azimuth dimension; and

adjusting the beam of both entities according to their respective second correction factors wherein an error is detected in the elevation dimension.

18. (Currently amended): A method for coordinating the use of beam forming between two communicating entities wherein control information regarding the use of beam forming is communicated between the two entities, the method comprising the steps of:

selecting a correction factor for each of the entities wherein the sum of the two correction factors is equal to one;

each entity measuring an error in the alignment of beams emanating from the two communicating entities; and

adjusting the beam of both entities according to their respective correction factors and error measurement, whereby the adjusted beams are aligned with beams emanating from the two communicating entities are aligned with respect to each other.

Applicants: Goldberg et al.
Application No.: 10/730,671

19. (Original): The method of claim 18 wherein the two communicating entities are a base station and a WTRU.

20. (Original): The method of claim 18 wherein the two communicating entities are two WTRUs.

21. (Original): The method of claim 18 wherein the error measurement and beam adjustment is performed in the azimuth dimension.

22. (Original): The method of claim 18 wherein the error measurement and beam adjustment is performed in the elevation dimension.

23. (Original): The method of claim 18 wherein the error measurement and beam adjustment is performed in the azimuth and elevation dimensions.

24. (Original): The method of claim 18 wherein the correction factor of one entity is zero thereby causing said entity to refrain from adjusting its beam.

25. (Currently amended): A wireless communication system wherein beams may be adjusted to enhance wireless communications between wireless entities operating in the system, the wireless communication system comprising:
a plurality of wireless entities, said entities being capable of communicating using beam formed transmission and reception patterns and including a processor for measuring an error in the alignment of their own beam and the beam of another entity with which they are communicating;

Applicants: Goldberg et al.
Application No.: 10/730,671

wherein at least one of two communicating wireless entities adjusts its beam a fraction of the error measured in the alignment of its beam with respect to the beam of the other wireless entity whereby the transmitted beams are aligned with each other.

26. (Original): The wireless communication system of claim 25 wherein the processor of the at least one communicating wireless entity is configured to adjust the beam of the at least one wireless entity in an amount equal to the fraction multiplied by the error measured.

27. (Original): The wireless communication system of claim 26 wherein a first of the two communicating wireless entities includes a transmitter configured to transmit the fraction to a second of the two communicating wireless entities.

28. (Original): The wireless communication system of claim 27 wherein the second wireless entity includes a receiver configured to receive the fraction and further includes a processor to adjust the beam of the second wireless entity in an amount equal to one minus the fraction multiplied by the error measured.

29. (Original): The wireless communication system of claim 28 wherein the first wireless entity is a WTRU and the second wireless entity is a WTRU.

30. (Original): The wireless communication system of claim 28 wherein the first wireless entity is a WTRU and the second wireless entity is a base station.

Applicants: Goldberg et al.
Application No.: 10/730,671

31. (Currently amended): A wireless transmit/receive unit (WTRU) configured to maintain alignment of its beam with the beam of another wireless entity with which the WTRU is communicating, the WTRU comprising:

a first processor configured to measure an error in the alignment of a first beam emanating from the WTRU and a second beam emanating from the other wireless entity; and

a second processor configured to compute a ~~first fraction~~ correction factor that is a fraction of said measured error and adjust the first beam in an amount equal to the ~~first fraction~~ correction factor multiplied by the error measured whereby the adjustment is less than or equal to 1 and said first beam is aligned with said second beam.

32. (Original): The WTRU of claim 31 further comprising:

a transmitter configured to transmit the fraction of the measured error that the WTRU will adjust its beam to the wireless entity with which the WTRU is communicating.

33. (Original): The WTRU of claim 32 further comprising:

a receiver configured to receive, from the wireless entity with which the WTRU is communicating, a second fraction with which the entity used to adjust its beam; and

wherein when a second fraction is received, the second processor being configured to compute the first fraction by subtracting one minus the second fraction and adjusting the first beam in an amount equal to the first fraction multiplied by the error measured.

Applicants: Goldberg et al.
Application No.: 10/730,671

34. (Original): The WTRU of claim 33 wherein the wireless entity with which the WTRU is communicating is another WTRU.

35. (Original): The WTRU of claim 33 wherein the wireless entity with which the WTRU is communicating is a base station.